US009636806B1

(12) **United States Patent**
Lee et al.

(10) **Patent No.:** **US 9,636,806 B1**
(45) **Date of Patent:** **May 2, 2017**

(54) **MULTIPLE SIZE NUT DRIVER**

(71) Applicants: **David M. Lee**, Westminster, CA (US);
Mike Zwiesler, Pasadena, CA (US)

(72) Inventors: **David M. Lee**, Westminster, CA (US);
Mike Zwiesler, Pasadena, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 477 days.

(21) Appl. No.: **14/504,294**

(22) Filed: **Oct. 1, 2014**

Related U.S. Application Data

(63) Continuation-in-part of application No. 14/275,411,
filed on May 12, 2014, now Pat. No. 9,573,252.

(51) **Int. Cl.**
B25B 13/00	(2006.01)
B25B 13/10	(2006.01)
B25B 13/06	(2006.01)
B25B 23/00	(2006.01)
B25B 23/16	(2006.01)

(52) **U.S. Cl.**
CPC **B25B 13/102** (2013.01); **B25B 13/06**
(2013.01); *B25B 23/0035* (2013.01); *B25B*
23/16 (2013.01)

(58) **Field of Classification Search**
CPC B25B 13/102; B25B 13/105; B25B 13/06;
B25B 23/16
USPC 81/124.5
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,346,061	A	7/1920	Rosenberg	
1,896,949	A	2/1933	Greiner	
3,285,106	A	11/1966	Svenson	
6,330,844	B1	12/2001	Walker	
6,467,379	B1	10/2002	Wizman	
6,637,298	B1 *	10/2003	O'Brien	B25B 13/102
				81/185
6,732,615	B2 *	5/2004	Layaou	B25B 13/102
				81/124.5
7,150,209	B1	12/2006	Loomis	

OTHER PUBLICATIONS

Select-a-Socket Multi Wrench, sold by GadgetsGo.com, http://
gadgetsgo.com/Multiple-head-socket-ratchet-tool.html, and https://
www.youtube.com/watch?v=VetyKs62k6l, Jan. 29, 2013.

* cited by examiner

Primary Examiner — Bryan R Muller
(74) *Attorney, Agent, or Firm* — Quickpatents, LLC;
Kevin Prince

(57) **ABSTRACT**

A nut driver for driving nuts of various sizes includes an
elongated housing with opposing driver and handle ends.
The driver end is open and assumes a largest size. A rigid
collar and plunger are fixed about the housing and posi-
tioned at any of a number of selectable radial positions, each
of which is associated with a different nut size. A plurality
of nested sockets are each slidably movable by the plunger
between forward and rearward positions. Each socket has a
foot adapted for contacting the plunger at one of the select-
able radial positions. The elongated housing is preferably
separated into two sections, including a handle and a two-
sided socket mechanism that includes two opposing driver
ends each having sockets of different sizes.

18 Claims, 5 Drawing Sheets